



China Abec 9 Bearing Supplier



16002 Bearing 2D drawings and 3D CAD models

Koyo Bearing 16002 6002-2ru 6202-2ru 6302-2ru

Bearing No. 16002

Size	15x32x8 mm
Bore Diameter	15 mm
Outer Diameter	32 mm
Width	8 mm
d	15 mm
D	32 mm
B	8 mm
C	8 mm
r min.	0,3 mm
da min.	17 mm
Da max.	30 mm
ra max.	0,3 mm
Weight	0,025 Kg
Basic dynamic load rating (C)	5,6 kN
Basic static load rating (C0)	2,85 kN
(Grease) Lubrication Speed	23000 r/min
(Oil) Lubrication Speed	28000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0



China Abec 9 Bearing Supplier

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	15MM Bore; 32MM Outside Diameter; 8MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.koyousa.com
Weight / LBS	0.05511
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.315 Inch 8 Millimeter
Bore	0.591 Inch 15 Millimeter
Outside Diameter	1.26 Inch 32 Millimeter
Bearing No.	16002
r(min)	0.3
Cr	7.00
C0r	2.85
Cu	0.150
f0	13.9



China Abec 9 Bearing Supplier

Grease lub.	23000
Oil lub.	28000
da(min)	17
Da(max)	30
ra(max)	0.3
(Refer.)Mass(kg)	0.025